



## Operation


Flip open the rear document support plate to improve flattening the laminate and it helps to prevent document jam occurrence.





Insert squarely the pouch, with the closed end first, into the paper inlet.

Once document jam occurs, turn OFF the machine and press the JAM RELEASE BUTTON all the way down until you hear a very significant "click" Hold firmly the machine in place and pull the document out from the paper inlet until it is fully retracted.



## Specification

Description	Re L 301 Premium	Re L401 Premium
Operating Voltage	220 ~ 240V, 50 Hz (or 120V, 60Hz for North America)	
Current	2.2A (4.3A)	1.3A (2.0A)
Dimensions, m,m (LxWxH)	451 x 183 x 108	340 x 140 x 84
Net Weight (kgs)	6.08 kgs	2.1 kgs
Max. Laminating Width	330mm	230mm
Pouch thickness range, microns	Minimum 50, Maximum 200	
aminating Speed	300 mm/minute	
Temperature Control	Not Available	
Narm up time, minutes	12	4 to 8
Recommended Duty Cycle	30 min. ON/30mim. OFF after READY lighted up	



**OFFICE & FACTORY** 

## Rakesh Enterprises

Plot No. 780, Defence Colony Sainikpuri, Secunderabad - 500 094. Ph: 0091-40-27111126, Fax: 27117099